



Pyroglaze 30 Intumescent Glazing Seal

Pyroglaze 30 seals are self-adhesive, pvc encapsulated strips of intumescent and provide proven 30 minute protection for glazed doors, screens and partitions.

In the event of fire, the intumescent swells to form a seal within the glazing pocket and also reduces the risk of premature ignition of the glazing beads on the protected face.

The system is easily installed and suitable for any shape of aperture as well as larger glazed panels.

Features and Benefits

- Tested in conjunction with a wide variety of glasses to include both integrity (E) and integrity/insulation (EI) glass types
- Successfully assessed by numerous UK and international testing centres
- Can be used with either softwood or hardwood systems
- Choice of standard colours – white, light and dark brown, light grey and slate grey, black, cream and red
- Pyroglaze 30 is manufactured as 10mm x 3mm with a choice of standard lengths – 1000mm, 1050mm, 2050mm, 2100mm
- Non-standard colours and lengths available on request
- Dry glazing system, no cleaning down after installation
- Can be supplied without PVC sleeving upon request and for circular & shaped glazing profiles & applications

Pyroglaze 30 Intumescent Glazing Seal

Description

Pyroglaze 30 seals comprise of self-adhesive semi-rigid pvc encapsulated strips, which are easily located between a fire resisting glass and untreated timber glazing beads. The system is simple, quick and clean and needs no cleaning down after installation.

Performance

Pyroglaze 30 seals have been fire tested/assessed in accordance with BS 476 Part 22 in conjunction with numerous glasses, for full details contact our Technical Department.

When subjected to a fully developed fire situation, the intumescent core swells to provide an effective seal within the glazing pocket, and also reduces the risk of premature ignition of the glazing beads on the protected face.

Application

Pyroglaze 30 seals can be used for glazing fire resisting screens, partitions, and fire rated doors.

Mann McGowan standard colours



Construction

When constructing glazed screens, all timber must have a density of approximately 650kg/m³.


The geometry of the glazing beads depends on the glass type. Our Technical Department can provide full information on request.

Mainframes should be securely fixed to the structure and then fire-stopped using the following alternatives:- Pyromas A (10mm deep), 2No. Pyrostrip 500 PSA 20mm x 4mm, or Pyrospan.

Pyroglaze 30 is fitted to the glazing beads by peeling off the release paper on the self-adhesive face of the strip and bonding into position.

Glazing beads should be secured into position using either 38mm long steel screws or pins at 200mm centres. In both cases, the fixings should be splayed to pass underneath the glass.


Pyroglaze 30 Glazing seals within shaped apertures



Maximum diameter 500mm




Maximum diameter 500mm



Straight edges not to exceed 500mm



Straight edges not to exceed 500mm



Length not to exceed 500mm

Note: Larger apertures may be possible. Please refer to our Technical Department for full details

Ordering

All Mann McGowan products can be ordered directly from our sales team on:

+44 (0) 1252 333601

or by email:

sales@mannmccgowan.co.uk

Technical Services

Email: technical@mannmccgowan.co.uk

Mann McGowan can advise on the use and application of any of our products.

We can also provide presentations or attend site surveys at your request.

Our quality management system is registered in accordance with ISO 9001:2015 by SGS Ltd.

The contents of this document are copyright throughout the world and may not be reproduced without prior written permission of Mann McGowan Fabrications Ltd. Information in this document is provided for guidance and does not form any part of any contract.



MANN McGOWAN
Intumescent Fire Smoke & Acoustic Seals

Mann McGowan Unit 4, Brook Trading Estate, Deadbrook Lane, Aldershot, Hampshire GU12 4XB England
Telephone: Aldershot +44 (0) 1252 333601 • Fax: Aldershot +44 (0) 1252 322724 • Email: sales@mannmccgowan.co.uk

www.mannmccgowan.co.uk